



Pipe Size	Opening Front (Pipe I.D.)	Opening Back	Back Wall (Inside)	Width of Open End	PS-2 Height	PS-2 Length	Mass (Top)	Mass (Bottom)
Nom	Ai	Ao	B	C	D	E	kg	kg
600	610	880	1219	2532	1623	2750	7,733	7,434
675	686	960	1219	2532	1623	2750	7,654	7,434
750	762	1050	1219	2532	1623	2750	7,554	7,434
825	838	1140	1219	2532	1623	2750	7,452	7,434
900	914	1230	1829	3463	2039	3350	12,652	9,627
975	991	1320	1829	3463	2039	3350	12,526	9,627
1050	1067	1410	1829	3463	2039	3350	12,394	9,627
1200	1219	1590	1829	3463	2039	3350	12,103	9,627
1350	1372	1760	2438	4072	2709	3350	17,106	10,639
1500	1524	1940	2438	4072	2709	3350	16,724	10,639
1650	1676	2120	2438	4072	2709	3350	16,308	10,639
1800	1829	2320	2438	4072	2709	3350	15,832	10,639

Headwall 600 to 1800mm Pipe

Notes

1. Precast alternative to OPSD 804.040.
2. Designed in accordance with CSA S6 - CHBDC.
3. Headwall grates as shown are available upon request.
4. All dimensions are in millimeters unless otherwise shown.
5. Alternate openings are available upon request.

